



NOTES:
1.PERFORMANCE CHARACTERISTICS: REFER TO KOLLMORGEN CATALOG
2.SHAFT SEAL: NONE
3.BRAKE: INSTALLED, REFER TO KOLLMORGEN CATALOG






MOTOR WIRING



ENCODER WIRING




NO	Signal	Color
1	U	Red
\equiv	GND	Green
3	W	Black
4	V	White
A	BRAKE 24V	thin white
B	BRAKE 0V	thin white
C		
D		

NO	SIGNAL	COLOR
1	B+	green
2	B-	g/blk
3	A-	blue
4	A+	blue/blk
5	Z+	yellow
6	Z-	y/blk
7	Gnd	black
8		
9		
10	+5V	red
11		
12		
13		
14		
15	Hall U+	brown
16	Hall V+	gray
17	Hall W+	white



This drawing contains PROPRIETARY information and is the property of KOLLMORGEN. This drawing may not be copied or used without prior written approval of KOLLMORGEN

INTERPRET GEOMETRIC SYMBOLS PER ANSI Y14.5M-1982

		UNLESS OTHERWISE SPECIFIED: DIMENSIONS APPLY BEFORE COATINGS REMOVE ALL SHARP BURRS AND BREAK ALL SHARP EDGES		
	SIGNIFICANT PRODUCT CHARACTERISTIC	MILLIMETER VALUES: WHOLE NUMBER X:±0.5 ONE PLACE X.X:±0.2 TWO PLACE X.XX:±0.05 ANGLES X°:±30'	[INCH] VALUES: WHOLE NUMBER X:±0.0197 ONE PLACE X.X:±0.00787 TWO PLACE X.XX:±0.00197 ANGLES X°:±30'	
		CRITICAL PRODUCT CHARACTERISTIC	DO NOT SCALE DRAWING USE DIMENSIONS ONLY ALL DIMENSIONS ARE MM [INCH] INCH DIMENSIONS IN BRACKETS [] ARE FOR REFERENCE ONLY	DRAWN BY: LZQ
THIRD ANGLE PROJECTION		CHECKED BY: SL		DATE: July 17, 2015
			APPROVED BY: JK	DATE: July 17, 2015

KOLLMORGEN		Design Control Location: 28 Weiwu Road Xiqing District, 300385 Tianjin, China	
MOTOR, AC SERVO CKM15C-AKC22-00			
SIZE B	CAGE CODE —	DWG. NO. CKM15C-AKC22-00	REV —
SCALE	1:5	SHEET 1 OF 1	